



Sistemi di illuminazione per quadri elettrici.  
Cabinet lighting systems

Approvals: CE

### Dati tecnici - Technical data

Guscio - Housing	Plastica bianca - White plastic
Classe - Appliance class	Doppio isolamento (classe II) - Double insulation (class II)
Collegamento elettrico - Electrical connection	Cavo 1,8m con spinotto (incluso) - 1,8m cable with plug (included)
Montaggio in serie - Serial Mounting	con il cavetto maschio (incluso)- With male cable (included)
Grado di protezione - Protection degree	IP20
Temperatura di stoccaggio - Storage temperature	-20°C / +60°C
Temperatura di funzionamento - Operating Temperature	-10°C / +50°C
Durata - Service life	20000h at 25°C
Connessione elettrica - Electrical connection	Connettore - Connector



Sistemi di illuminazione per quadri elettrici.  
Cabinet lighting systems

Code	Light source LED (K)	Luminous Flux (lm)	Voltage (V) and Frequency	Watt (W)	Dimension			Turn on
					A	B	C	
EX LL23BS4WLC	6500	428	230VAC 50/60Hz	4	288	30	22	Switch ON/OFF
EX LL23BS6WLC	6500	595	230VAC 50/60Hz	6	370	30	22	Switch ON/OFF
EX LL23BS9WLC	6500	823	230VAC 50/60Hz	9	425	30	22	Switch ON/OFF
EX LL23BS14WLC	6500	1303	230VAC 50/60Hz	14	622	30	22	Switch ON/OFF

### Disegno tecnico - Technical drawing

